

June 11, 2013

Firmware Release Notes

MultiMAX®

MultiMAX Firmware Upgrade to version 7.51

340.00 - 354.00 MHz, FCC/IC

433.42 - 434.42 MHz, CE

Documentation includes

(in order):

- Firmware Release Notes 7.51
- Firmware Release Notes 7.5
- MultiMAX manual v1.5

Note: These release notes apply to firmware upgrade 7.51 or higher.

MultiMAX Firmware 7.51 Overview

Intro: MultiMAX firmware version 7.51 adds two new features introduced since the launch of firmware version 7.500: Patterns and Auto Power-Off control.

IMPORTANT:

This new firmware requires that you use PocketWizard Utility version 1.54 or later. It is available for download [here](#). Upgrade to the latest Utility first, then upgrade your radios' firmware.

When you have installed the latest Utility, follow these steps to connect your MultiMAX to the computer:

1. Turn off the MultiMAX
2. Hold the backlight button (between TEST and MENU).
3. Continue to hold backlight, and connect the radio to your computer with a standard Mini-B USB cable.
4. Continue to hold backlight, and set the power switch to TRANSMIT.
5. Release the backlight button, then click "Check for Updates" in the Utility to begin.

When updating firmware, be sure to update all of your radios to the latest version, 7.51. Your radios will only operate as expected when all units are using the latest firmware.

PocketWizard Utility and Factory Reset Note: Always perform a factory reset after updating your firmware. The PocketWizard Utility performs a factory reset automatically when you upgrade the firmware. It also has a Factory Reset button on the Update tab which additionally simplifies factory reset. You can also perform a Factory Reset with the radio: to reset your MultiMAX to factory defaults, hold "C" as you power on the radio.

Custom IDs: If you have Custom IDs installed in your MultiMAX, they will be retained through a firmware upgrade and factory reset. Custom IDs are permanent.

Learn More: Visit the [PocketWizard Wiki](#) for more information on using your radios.

Overview of New Key Features:

- Patterns
- Auto Power-Off Control

New Key Features:

Patterns:

MultiMAX firmware 7.51 or later has a feature called Patterns. Patterns help when there are multiple photographers triggering on the same frequency. When you press and hold TEST on your MultiMAX, repeated triggers are being sent at a steady pace. If your triggers overlap with another photographer's, neither of your remote cameras will fire. Patterns help prevent repeating triggers from overlapping and dramatically reduce the possibility of triggers on the same frequency cancelling each other out.

This feature benefits:

- FCC MultiMAX radios with Custom IDs installed
- CE MultiMAX radios with or without Custom IDs installed

FCC MultiMAX radios without Custom IDs do not support this feature.

Patterns are only helpful for remote camera triggering. They are not helpful for remote flash triggering.

To learn about Custom IDs, visit our PocketWizard wiki page on [Multiuser Environments](#).

Patterns are only available for USB MultiMAX radios, FCC or CE. MultiMAX radios without USB ports cannot take advantage of Patterns.


For FCC radios, there can be multiple Custom IDs triggering on the same frequency at very large sporting events. Your Custom ID will prevent someone else from triggering your camera, but it won't prevent someone else from stepping on your trigger signal and potentially canceling out the triggers. You need Patterns.

For USB FCC MultiMAX radios with Custom IDs, Patterns are set under the Other Functions / Custom ID menu. This menu only appears if you have Custom IDs installed in your USB FCC MultiMAX with firmware 7.51 or later.



For CE radios, with or without Custom IDs, channels 17-32 share the same frequency and each channel has its own digital code. Your channel or Custom ID will prevent someone else from triggering your camera, but it won't prevent someone else from stepping on your trigger signal and potentially canceling out the triggers. You need Patterns.

For USB CE MultiMAX radios, with or without Custom IDs, Patterns are handled differently. Channels 17 – 32 are all on the same frequency already due to CE frequency regulations, so Patterns are available without Custom IDs installed. Select a Pattern under the Other Functions/Custom ID menu, and make sure to set a different channel or Custom ID from other CE photographers.



General Notes about Patterns:

Patterns should be set on both the transmitting and receiving radios.

You can combine Patterns and Long Range Mode.

Confirmation works differently when using Patterns or Long Range Mode. There are two kinds of confirmation: ping and trigger. See page 21 in the [MultiMAX manual](#) for more information on confirmation.

Ping: By toggling a Zone on and off on your transmitter, you can test for full round trip radio communication. If the Zone letter does not display as inverse video when you toggle it on, that is a good confirmation. If it does display as inverse video (has a black box around it) then take steps to improve your radio reception.


Trigger: When using Patterns or Long Range Mode, trigger confirmation is not performed. This is to reduce the number of radio signals in the air which helps in [Multiuser Environments](#). Your zone will display as inverse video (has a black box around it) after a trigger, but this is not an indication of success or failure.

Auto-Power Off Control:

MultiMAX firmware 7.51 or later allows you to control if your radio will automatically power off when using batteries. Previously, your USB MultiMAX would turn off after 40 hours to protect the batteries. Now you can set your MultiMAX to stay on battery power as long as possible.

Auto Power Off is set via the Other Functions Menu. If you select "SET ALWAYS ON" then your MultiMAX will run as long as it can on a set of batteries. When "AUTO POWER OFF" is set (default), the MultiMAX will turn itself off after 40 hours of receiving no triggers. This saves some percentage of your batteries so you can still get some use out of the radio if you left it turned on accidentally.

When powering your firmware version 7.51 MultiMAX with an AC Adapter, your radio will not automatically power off. It will be powered by the AC adapter even if there are batteries installed. If there are batteries installed and the AC adapter loses power, the MultiMAX will automatically switch to battery power and it will obey the Auto Power Off setting. The AC adapter does not charge your batteries.



© 2013 LPA Design, Inc. All rights reserved. Product features and specifications are subject to change without notice. PocketWizard, ControlTL, MiniTT1, FlexTT5, HyperSync, Plus II, Plus III, PlusX and MultiMAX are either trademarks or registered trademarks of LPA Design, Inc. All other trademarks contained herein are the property of their respective owners.

This product is covered under a warranty. For more information on this warranty and to register your product, please go to www.PocketWizard.com/support.

US Patent: www.pwpatents.com
US and other patents pending.

Owner's Manual Addendum

Including: MultiMAX Firmware Upgrade v7.5 (for USB-enabled FCC/CE MultiMAX radios only)

Special Note for CE MultiMAX Owners

MultiMAX Firmware Upgrade v7.5

MultiMAX 7.5 is packed with new features and capabilities for the MultiMAX user including a new Long Range Mode for remote camera triggering, which beta testers found particularly useful in arenas and other challenging remote camera applications. Additionally, you can now move your Custom ID to any PocketWizard frequency for better triggering in crowded shooting environments. Multi-Zone Receive allows you to select more than one zone for receive, useful when sharing lights.

The new Signal Strength Indicator provides a quick view of local noise levels when the unit is turned on then switches to indicate the strength of the last trigger received. When you need to fully understand your shooting environment, the Noise Sniffer allows you to see the noise level on every channel. This allows you to locate potential interference and switch channels before it becomes a problem.

There's more and you can read the details for all new features and capabilities on the following pages.

NEW FEATURES:

- Long Range Mode for remote camera triggering
- Close Range Mode for working at extremely close distances
- Toggle the hot shoe on and off
- Custom ID Move - put your CID on a different frequency!
- Multi-Zone Receive
- Signal Strength indicator
- Menu indicator for longer menus
- Noise Sniffer
- Radio Relay (Repeater) Mode

Range Menu - */MENU L A



A:RANGE MODE

Long Range Mode - */MENU L A A

A:LONG-LT/LR

Long range mode increases the usable distance, up to double, between two MultiMAX radios. This new feature is ideal for photographers shooting sports or wildlife, or anyone who simply needs long range remote camera capability.

This mode must be activated on all radios that are expected to work together. When it is activated on a transmitter, **LT** will be displayed. When it is activated on a receiver, **-LR-** will be displayed. This mode is designed primarily for remote camera triggering. It can also be used for remote flash triggering at shutter speeds up to 1/125th. This mode cannot be used with the Plus II, Sekonic meters, or flash packs with a PocketWizard radio built in.



Engaging Long Range Mode will automatically adjust default contact time to 0.12 seconds.

NOTE: Long Range Mode is only for MultiMAX channels 17 through 32. Trigger confirmation is not available in Long Range Mode.

Normal Range Mode - */MENU L A B

B:NORMAL-TX/RX


Normal mode sets your MultiMAX to work at standard distances on regular channels. This is the default operation for your MultiMAX. This mode must be activated on all radios that are expected to work together. When it is activated on a transmitter, **TX** will be displayed. When it is activated on a receiver, **-RX-** will be displayed.



Close Range Mode - */MENU L A C (Transmitter Only)

C:CLOSE-CT

Close range mode reduces the transmit power of your MultiMAX when it is in TRANSMIT mode. This mode is useful if you have a receiver very close to your transmitter (within a few feet). Normally it is recommended to keep several feet between a transmitter and a receiver. When working with radios very close together, like on a basketball net, the transmitter can overwhelm the receiver. Close Range Mode helps correct that situation.



Close Range Mode is only set on a transmitter, not on a receiver. When it is activated on a transmitter, **CT** will be displayed. The receiver must be set to Normal Range Mode. -RX- will be displayed on the receiver. This mode is not compatible with Long Range Mode. This mode can be used with a MultiMAX, Plus, Plus II, flash packs with integrated PocketWizard radios or FlexTT5 as Receiver (standard channels only).

Hot Shoe Menu - */MENU L B

B:HOTSHOE OFF

Toggle the hot shoe on or off as needed. Press */MENU L B. Display will show "Hotshoe Input Disabled". Toggling the hot shoe input to OFF may be useful when mounting the MultiMAX on a cold shoe, or when you desire the trigger input to come from PORT 1 and not the hot shoe it is mounted in. Press */MENU L B again and the display will read "Hot shoe Input Enabled".



Custom ID Menu - */MENU L C

C:CUSTOM ID

This menu only appears if you have a Custom ID and you have a US/FCC radio.

What is a Custom ID? It is a private channel on a MultiMAX. In hyper-crowded shooting environments, Custom IDs give you the confidence to know that your remote flash or camera can only be triggered by you and not any other photographer. It is an exclusive code installed on top of an existing PocketWizard frequency, usually replacing Channel 17 with your new custom code and frequency combination.

No other manufacturer offers such a unique and valuable service. Because Custom IDs require a firmware modification, this service is only available directly through LPA Design. Contact us via our inquiries page on:

PocketWizard.com: <http://www.pocketwizard.com/contact/inquiry/>

Move Custom ID Frequency - */MENU L C A

A:CUSTOM ID FREQ

Use this menu to move your Custom IDs to a different frequency. This is useful if there is RF noise on your Custom ID's default frequency (see "Noise Sniffer" for more information) or if another user has a Custom ID on your default frequency.



Select the Custom ID you want to move to a different frequency by pressing A or B. Only Quad-Triggering Channel IDs (Channels 17 - 32) can be moved. Only your first 2 Custom IDs can be moved.

On the next screen you will see: SAME AS CHAN XX and a number.

The number is the frequency - $349.000 = 349.000$ MHz. Using the arrow keys, move your Custom ID to the frequency you want and press */MENU. Every frequency is shared by a MultiMAX Quad-Triggering Channel.



When the display says SAME AS CHAN 21 and the frequency displayed is 348500 that means that your Custom ID will use the same frequency that is in use on standard Channel 21 - Photographers using that channel can't trigger you and you can't trigger them, but if you try to trigger at the exact same time then you may interfere with each other and cause a loss of triggers.

View Custom ID - */MENU L C B

B:VIEW CUSTOM ID

Displays a list of your installed Custom IDs and what frequency they are using.



Multi-Zone Receive (Receive Only)

The MultiMAX now allows you to select more than one Zone for receive. You can receive on any combination of Zones. If you select A and B, for example, any trigger on either A or B will trigger the radio. This feature allows another avenue of creative control for zones.

EXAMPLE: Two photographers are working the same venue. Each has their own portable flash system that they move with them, and they share area flashes that light the ceiling. One photographer could use Zone A for his nearby flashes while the other photographer uses Zone B. The receiver triggering the area flashes could be set to A & B.

Menu Indicator

If a menu in the MultiMAX contains more than four items, there is a now an indicator that shows there are more choices above or below the current list. Just use the arrow keys to see the other menu items.

Signal Strength Indicator (Receive Only)

The Signal Indicator (antenna level bars like on a cell phone) now performs two functions:

1. Noise Meter: If your radio has NOT been triggered, the Signal Indicator will show steady noise in the area. More bars = Good radio environment (less noise). If your Signal Indicator shows fewer bars then there is a strong source of constant interference in the area. The Signal Indicator will not show transient or brief interference like from another PocketWizard user. Noise Sniffer "SLOW" scan might help there.

2. If your radio has been triggered, the Signal Indicator shows the strength of the last trigger received. More bars = clear signal.

Noise Sniffer - */MENU B L (Receive Only)

L:NOISE SNIFFER

The Noise Sniffer is a MultiMAX tool for troubleshooting RF issues. It can show the relative radio noise for the MultiMAX channel and frequency displayed. To access the Noise Sniffer set the MultiMAX to RECEIVE then press */MENU B L.




In Noise Sniffer mode, use the arrow keys to cycle through the channels. If you have a Custom ID, it will use the correct frequency for your Custom ID channel.

Place the MultiMAX in a location you intend to use, or walk around with the MultiMAX to help pinpoint noise sources. Move the antenna closer to cable-runs and metal structures to see if they are sources of RF noise on your channel.

127 = maximum noise the MultiMAX can sense. Lower is better. Readings below 40 are unlikely. What "should" the numbers be? As low as possible and still have reliable operation. These numbers are only for comparing one channel to another or for verifying RF noise as a possible factor on your channel or location of choice. There is no perfect number, so operation needs to be evaluated in context with these numbers.

- **FAST Noise** – displays noise readings as fast as the MultiMAX can sample. If this number is consistently high, there is a strong interference source in the area. It samples so quickly, however, that brief transient noise is hard to note.
- **SLOW Noise** – displays the highest noise sample out of the last 150. This will help you see live transient or very brief noise like another PocketWizard radio triggering.
- **PEAK Noise** – displays the highest noise reading (FAST or SLOW) since you last cleared it or changed channels. This will help you see the highest noise moment, but it is not real time. It is good for catching the most transient of interference or as a reference when evaluating a better location. Reset using the A key.



When all three numbers are roughly equal, this represents the base line RF noise for that channel in that location. Lower is better. Choose a channel with less noise or move to a less noisy area.

If FAST is low compared to SLOW or PEAK then there may be transient RF noise in the area. Something is probably creating RF noise on the channel but it is only happening sporadically. If possible, use another channel or move away from the interference source. If SLOW only shows occasional spikes, you may be fine.


If the unit's LED blinks in any manner other than the normal "powered on" blink (once every two seconds), then the source of the noise is another PocketWizard on your frequency!

A MultiMAX mounted near the ground (within a few feet) may display a low noise reading and still have poor performance. This is because the ground absorbs radio energy. It absorbs the signal from your PocketWizards, so performance worsens in general. It also absorbs the ambient RF noise so the MultiMAX Noise Sniffer shows less noise present. In this situation a small amount of RF noise might have a much more extreme effect on reception reliability as one problem exacerbates the other.

Radio Relay (Repeater) Mode (Receive Only)

This mode lets you deploy another MultiMAX to increase your range. It receives and transmits on the same channel.

To activate Radio Relay (Repeater), set the MultiMAX to RECEIVE on your channel of choice, then press the “L” key twice. You should now see RPT on the display.



Pressing “L” toggles between these modes:

- RLY = Standard Camera Relay. It also displays the channel to be used when Transmitting. This is set in TRANSMIT mode. Read more about Relay Mode in your MultiMAX manual.
- RPT = Radio Relay (Repeater). There is no transmit channel to set in this mode. It uses the channel as displayed in the upper right.
- No relay function (off = no display). The radio operates only as a receiver.

Make sure the zone of the repeater is set to one you are using on your transmitter. You can use all of the other zones on your transmitting unit and the RPT MultiMAX will relay your selected zones as long as it is also on one of the selected zones.

Deploy the repeating MultiMAX where it effectively triggers the remote unit, and can be effectively triggered by your transmitting unit.

IMPORTANT: Do not deploy more than one repeater to cover the same remote. Extra repeating units will step on each other and make it difficult for your remote to get a trigger – bathing an area with repeaters is likely to worsen the remote's performance. You can use additional units to further increase the distance from your remote, but each repeater should be deployed to cover only one leg of the journey. Each repeating unit increases the radio delay by ~0.0018 seconds (~1/800). If you are using the RPT unit for remote camera triggering, this small delay will be unnoticeable. If you are using the RPT unit for remote flash triggering, this may affect the fastest shutter speed you can use.

Suggestions for remote camera triggering:

Eliminate as many RF interference issues as possible.

- Maintain a line of sight between the units.
- Keep the antennas parallel and at least 12" apart.
- Make sure the radios, and especially the antennas, are not near any large metal, concrete, or high water-content objects. People and trees are mostly water! Make sure they are not blocked by these objects or by hills. Crowds gathering between you and your remotes will reduce range. Try to keep the antennas above the heads of crowds.
- PocketWizard radios will have reduced performance if deployed close to the ground. Try to get them up high – 4 feet or higher improves range dramatically. Consider using any miniphone/headphone extension cable (including a PocketWizard MMX cable) to locate the receiver higher up.
- Avoid mounting them to long metal railings or other building structures.
- Avoid mounting them near long cable runs for other equipment or close to building wiring.
- Do not wrap connecting cables around the antenna. Keep them away from the antenna. Use right angle connectors whenever possible.
- Do not affix the radio by taping the antenna to something. Especially, do not use duct tape or any tape containing metal fibers on the antenna.
- Avoid using long cable runs with PocketWizard radios. If you must use a long cable run, deploy ferrite chokes (<http://www.radioshack.com/product/index.jsp?productId=2103222>) near the PocketWizard end of the long run. Use more than one ferrite choke when possible. Place them 6 to 12 inches from the radio and from each other.
- “Dead spots” have a number of causes, but the solution is usually the same: move the unit a few inches or feet away from the problem area.

For remote “finish line” cameras or any remote camera where a long motor drive burst is desired, consider the following:

- Set a long contact time (for example, 1.50 seconds) on the remote receiving unit. If range is an issue or remote operation is intermittent, this will help. If any single trigger is received, a long burst is guaranteed. Contact time is set by pressing * B A.
- Trying to get a remote camera to trigger as fast as the master camera in your hands by having the transmitting PocketWizard connected to the shoe or PC of the master may be problematic. Cameras are not designed to be triggered like a high speed hot shoe flash – for example five very short triggers in under one second. This may confuse the remote camera, cause it to not trigger, or cause it to trigger sporadically. Instead of relying on the shoe trigger, use either:
 - » A button cable (BT1 or BT3) connected to PORT 1 of the transmitting unit. Tape this button to the grip of the master camera.
 - » A –P cable (pre-release/pre-trigger cable) connected from the motor drive of the camera in your hands to PORT 1 of the transmitting MultiMAX. This causes the transmitting unit to be triggered as you press all the way down on your camera’s shutter release. You must use a –P cable and it must be set to OFF for this to function properly.

PocketWizard Utility

Your MultiMAX has a USB port which allows it to be easily updated to the latest firmware using the PocketWizard Utility. The PocketWizard Utility can be downloaded on our website at <http://www.PocketWizard.com/support/downloads/>

To connect your USB-enabled MultiMAX to your computer, please follow these steps:

1. Turn off the MultiMAX radio and make sure you have fresh batteries installed.
2. Press and hold the backlight key (located between MENU and TEST) as you turn the MultiMAX on to TRANSMIT.
3. Note that the STATUS LED blinks steadily and the LCD remains blank. This confirms the radio is in USB mode.
4. Make sure the PocketWizard Utility is running on your computer and no other PocketWizard radios are connected to it.
5. Connect your MultiMAX radio to your computer using a standard Mini-B USB cable and note that your MultiMAX radio appears in the PocketWizard Utility.
6. To update your radio, click "Check For Updates" in the Maintenance Tab. Most updates require a full factory reset (see the RESET section on Page 29 in your MultiMAX Owner's Manual). Be sure to write down any special settings like Contact Time, etc., before you update your radio.

Consider updating all the USB-enabled MultiMAX radios in your system to the same firmware. Older MultiMAX radios that do not have a USB port will continue to work as part of your MultiMAX system. The older non-USB radios cannot get the new features, but will still perform their original functions normally when paired with USB-enabled radios.

Special Note for CE MultiMAX Owners

The owner's manual included with your purchase refers to the US (344-354 MHz) model of the MultiMAX. The following adjustments or errata should be noted for proper operation of your CE (433 MHz) MultiMAX:

Page 18:

The CE MultiMAX is not compatible with the following products as these products were not produced on CE frequencies: 10 Channel Classic, 16 Channel Classic, PocketWizard MAX, and Calumet TurboFilter.

Page 50:

The PocketWizard Radio Frequencies table refers to USA frequencies. CE units do not operate on these frequencies and are not compatible with PocketWizard radios on these frequencies.

CE PocketWizard Radio Frequencies:

Channel	Frequency	Unit	Digital Code
1 - 16	433.62 MHz	Plus or MultiMAX	16 Bit
17 - 32	434.22 MHz	MultiMAX Only	24 Bit (20 Bit in FAST MODE)

© 2010 LPA Design, Inc. All rights reserved. Product features and specifications are subject to change without notice. PocketWizard, ControlTL, MiniTT1, FlexTT5, HyperSync, Plus II and MultiMAX are either trademarks or registered trademarks of LPA Design, Inc. All other trademarks contained herein are the property of their respective owners.

This product is covered under a warranty. For more information on this warranty and to register your product, please go to www.PocketWizard.com/support.

US Patent: 5,359,375 and Patents Pending
LPF657 v1.1

PocketWizard Multi**MAX**

Owner's Manual





Congratulations on the purchase of your new **PocketWizard MultiMAX** digital radio triggering system.

The **PocketWizard MultiMAX** is a microprocessor-based radio slave system that uses advanced digital signaling to increase triggering range, reliability and reject radio noise from other sources. Since it utilizes Transceiver technology, it is both a transmitter and a receiver all in one. It is the most innovative and advanced wireless solution in the photographic industry.

As a stand-alone unit, the **MultiMAX** offers precision special effects functions not available in any wireless triggering device. It incorporates integrated Trigger Time Control software, True Trigger Confirmation and Selective Quad Triggering, all of which offer solutions to photographic challenges that hinder today's photographer's creativity. Unparalleled in features and performance, the **PocketWizard MultiMAX** is more than just a radio slave.

Welcome to Digital Wireless Freedom!

Manufactured in the United States of America by:

LPA Design
21 Gregory Drive
Suite 140
South Burlington, VT 05403



TABLE OF CONTENTS

"The FCC Wants You To Know"	7
Icons Used in this Manual	8
Features	9
Communication Technology	9
Basic Features	9
Special Features	9
Part Reference	10
LCD Information	11
Controls	12
Power Switch	12
Keypad	12
PORT 1 / PORT 2	12
Status LED	12
Getting Started	13
Safety Warnings	13
Battery Information	13
Battery Life	14
Mounting	14
VELCRO®	14
1/4-20 Mount	14
Shoe Mount	14
Lanyard	14
Quick Setup - Basic Radio Slave Operation	15
Basic Setup for Remote Flash	15
Triggering Multiple Flashes With Multiple RECEIVE Units	16
Connecting MultiMAX (set for TRANSMIT mode) to Flash	16
Standard Radio Operation	17
Transceiver Control	17
Channels	17
Compatibility	18
Selective Quad-Triggering (A B C D keys)	19
Classic Channels	20
L Key	20



True Confirmation	21
Radio	21
Optional Flash Confirmation Cable	21
Menu System	23
Navigation	23
Numeric Entry	24
Main Menu	25
A: Advanced Menu	25
B: Basic Settings	25
C: Counter Menu	25
D: Go Advanced	25
D: Go Normal	25
Basic Settings	26
A: Contact Time	26
B: Beep Menu	28
A: Beep on All	28
B: Beep on Trigger	28
D: Beep Disable	28
C: LCD Contrast Adjustment	29
D: RESET	29
Counter Menu	30
A: Count Up + Reset	30
B: Count Down + Reset	30
C: Clear / Reset	30
D: Disable	30
Advanced Menu	31
A: Delay Menu - TRANSMITTER	31
A: Remotes + PORT 2	31
B: Remotes Only	32
C: Rear Curtain	32
A: Delay Menu - RECEIVER	33
A: PORT 1 + PORT 2	33
B: PORT 2	33
C: Equalize	34
B: Intervalometer (Time Lapse Photography)	35
C: Multipop	36
D: SpeedCycler - TRANSMITTER	37
D: Fast Mode - RECEIVER	38



Other Features	38
Keypad Lock	38
High Voltage Protection	38
USB Port	38
Relay Mode	39
Software Version Display	39
Applications of Advanced Functions	40
Self-Timer or Cable Release	40
TTL / Auto flash Helper	40
Programmed Sequence Shooting	41
Recycle Lockout	41
Camera Equalization	42
Lag Time Measurement	43
One Unit Equalization	46
Two Unit Equalization	46
Equalization Adjustments	48
Technical Information	49
Specifications	49
Radio Information	50
Maximum and Minimum Settings	51
Saved Settings	51
Troubleshooting	52
When in doubt !	52
Reset to Default Factory Settings	52
Sustaining High Performance	53
Time Conversion Charts	54
Fractions to Decimal	54

*To find the correct **PocketWizard** brand cables for your flash and cameras, and to experience other products like the **Plus II**, please visit www.PocketWizard.com or your local photography dealer.*



⚠ This US frequency **MultiMAX** is compatible with all US frequency **PocketWizard** products. It is *not* frequency compatible with CE or JAPAN **PocketWizard** products. Verify frequency compatibility before purchasing. Some products are not manufactured on every frequency. Always operate within local radio regulations.

THE FCC WANTS YOU TO KNOW:

WARNING: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

1. Reorient or relocate the receiving antenna.
2. Increase the separation between the equipment and the receiver.
3. Consult the dealer or an experienced radio or television technician for help.


This device complies with Part 15 of the FCC rules and also with RSS-210 of Industry Canada. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Transceiver FCC ID Number: KDS-PW2-101

Transceiver Canada IC: 2170A-PW101



ICONS USED IN THIS MANUAL

 Read the information following this icon. It shows important notes about the subject being discussed.

 Follow this icon for more detailed information on the subject in another section.

 Find valuable tips and techniques with this icon.

 Warning or caution.

Refer to **www.pocketwizard.com** for updated information.



FEATURES

Communication Technology

- Full Digital Radio Communication
- Microprocessor controlled
- 32 digitally coded channels
- Complex 16 or 24 bit coded signal
- Selective Quad-Triggering

Basic Features


- Built-in hot shoe
- 1/4-20 female mounting thread
- Built-In AC adapter jack (see Page 49 for ordering information)
- Illuminated LCD panel
- Illuminated soft touch keypad
- 60 Hours battery life (depending on usage)
- Sync speeds up to 1/250 with focal plane shutter, 1/500 with leaf shutter
- Fast Mode syncs up to 1/1000 with compatible cameras and flashes
- Adjustable contact closure time
- Compatible with all US frequency PocketWizard products (see Page 7)
- Protects cameras from high sync voltage
- Customizable audible beep settings
- Weighs less than 5.5 ounces with batteries
- USB port for future upgrades

Special Features


- Transceiver Technology
- True Confirmation
 - Quad-Triggering Confirmation on all four zones*
 - Flash Confirmation with Optional Cable on all four zones*
- Trigger Time Controller Software
 - Rear Curtain Sync*
 - Precision Delays*
 - Intervalometer*
 - Multipop*
 - Lag Time Measurement*
 - Multiple Camera Equalization*
 - SpeedCycler*
 - Relay Mode*




MULTIMAX PART REFERENCE




LCD INFORMATION



Primary Display Area for Main Screen, Menus, Numeric Entry, etc.



TRANSMITTER
Default Power On Screen



RECEIVER
Default Power On Screen




MAIN MENU
Default Screen

CONTROLS


Power Switch


- **TRANSMIT** = Unit is powered on in TRANSMITTER (TX) mode
- **RECEIVE** = Unit is powered on in RECEIVER (RX) mode
- **OFF** = Unit is powered OFF



Power Switch

Keypad


- **A B C D L** = Selects Quad-Triggering Zones and Local. Also used in menu navigation and numeric entry
- **TEST** = Triggers MultiMAX. Press to test operation or to trigger remote units and/or attached cameras/flashes
-  Illuminates LCD and keypad. Hold down for key lock. Pressing it while in any menu will bring you back to the Main Screen.
- *** / MENU** = enters menus, and is used to enter or select items.
- **▲ ▼** Used for menu selection, selecting channels and numeric entry.



Keypad

Port 1 / Port 2

- **CAMERA / PORT 1** =
 - Input from camera sync terminal, external trigger button, Flash Confirmation Cable, or other device
 - Output to camera motor drive, flash, or other device
- **FLASH / PORT 2** = Output to flash, camera motor drive, or other device



Port 1, Port 2, Status LED

Status LED

Displays the following information:

- **Blinking every few seconds** = power on, ready for trigger
- **Blinking in sync with trigger** = normal triggering
- **Steady** =
 - continuously triggered from radio, hot shoe, or PORT 1
 - performing delay or contact time
- **Once every two seconds** = performing Intervalometer or Multi-pop function
- **Dark** = power off or poor battery condition



GETTING STARTED

⚠ Please pay attention to the following safety warnings:

- Operating temperature: above -15°C (5°F) and below 50°C (120°F)
- Storage temperature, without batteries: above -30°C (-22°F) and below 85°C (185°F)
- Remove batteries during storage.
- Battery Requirements: IEC:LR6 (AA) Size
- Do not remove instrument covers during operation.
- Do not operate the device in the presence of flammable gases or fumes. Operation of any electrical instrument in such an environment constitutes a definite safety hazard.
- There are no user serviceable parts inside the **MultiMAX**. Do not install substitute parts or perform any unauthorized modification of the instrument. Refer servicing only to qualified and authorized personnel.
- Red LED's are used for dim light application and do not indicate a hazardous status.
- The **MultiMAX** is an accessory device for cameras and flashes. Do not use this product in a manner not specified in documentation.

Battery Information

⚠ **CAUTION:** Turn OFF your equipment (**PocketWizard** units, electronic flash units, cameras, etc.) before making connections or changing batteries.

Install 2 fresh AA (IEC:LR6) batteries into the **MultiMAX**. Make sure to note proper polarity. Alkaline batteries are recommended. Rechargeable batteries will also work, though operation time may be reduced.



⚠ **WARNING** – To avoid battery leakage, follow these guidelines:

- Always remove the batteries when the unit is not in use for extended periods of time, or during shipping or long distance travel.
 - Never mix old and new batteries. Always use a fresh pair of matched batteries.
 - Always change batteries promptly at the first indication of low battery operation.
 - Do not use or leave the unit in extreme temperature or humidity situations.
- See “Technical Information” for normal operating and storage temperatures.

👁 Erratic unit behavior or malfunction may occur if batteries are inserted while the power switch is set to either RECEIVE or TRANSMIT. Always make sure the power switch is set to OFF before changing or inserting batteries.

Battery Life

The MultiMAX displays remaining battery life with a 3 segment battery icon in the upper left corner of the LCD:

3 segments displayed = batteries are fresh/new



2 segments displayed = batteries are good



1 segment displayed = replace batteries soon




0 segments displayed = install fresh/new batteries immediately



With one set of standard Alkaline batteries the MultiMAX will operate for approximately 60 hours. When using Intervalometer or Multipop modes exclusively, battery life can be 200 – 300 hours. This time may vary depending on temperature, battery type, and the quality of batteries used. Extensive use of back light, speaker, or extended trigger contact times will consume the batteries at a faster rate.

The MultiMAX continually regulates the battery power which gives excellent performance throughout the life of the batteries. The unit will continue to function normally until the batteries are nearly exhausted.

 The MultiMAX voltage regulation is very efficient. There is only a small benefit when using Lithium batteries. Lithium batteries are designed for the quick burst high current draw found in cameras and portable flash devices. Expect only a 10 - 20% longer battery life (approximate) over Alkaline batteries when using Lithium batteries.

MOUNTING

Mount a remote **MultiMAX** using any of the included methods.

See ***Sustaining High Performance*** (page 53) for more mounting information.

VELCRO®

For attaching to flashes, brackets, cameras, etc.



1/4-20 Mount

For tripods, mounting arms, isolation bars, brackets, etc.



Shoe Mount

For mounting on a bracket shoe, cold or dead shoe, etc.



Lanyard

For hanging from a light stand, flash handle, tripod knob, belt, etc.



QUICK SETUP - BASIC RADIO SLAVE OPERATION

Basic Setup for Remote Flash

- ▲ Turn off all equipment before installing batteries or making connections!
1. Install 2 AA batteries in each MultiMAX
 2. Connect camera to first MultiMAX:
 - a. Slide unit into camera hot shoe
- or -
 - b. Use sync cable to connect camera's PC terminal to CAMERA / PORT 1
 3. Connect flash to second MultiMAX
 - a. Use flash cable to connect flash unit's sync terminal to FLASH / PORT 2
 4. Turn both MultiMAX units on
 - a. Set power switch on MultiMAX attached to camera to TRANSMIT mode
 - b. Set power switch on MultiMAX attached to flash to RECEIVE mode
 5. Set both MultiMAX units to same channel and Quad-Triggering zone
 - a. Use ▲▼ to set channel (default is CH: 17)
 - b. Use **A B C D L** to select Quad-Triggering zones
(default is TRANSMIT = **A B C D L**, RECEIVE = **A**)
 6. Turn camera and flash on
 7. Press **TEST** button on MultiMAX (set for TRANSMIT mode) and release.
- Confirm remote flash triggers.
- You're all set! Use the camera normally.*

Triggering Multiple Flashes With Multiple RECEIVE Units

Multiple remote flash units may be triggered in sync with each other.

1. Install batteries in each additional MultiMAX unit
2. Use flash cable to connect each additional flash unit's sync terminal to FLASH / PORT 2
3. Set power switch on each additional MultiMAX unit to RECEIVE mode
4. Set all MultiMAX units to same channel as TRANSMIT unit

You're all set! Use the camera normally.

Connecting MultiMAX (set for TRANSMIT mode) to Flash

A flash can be connected to a MultiMAX (set for TRANSMIT mode). It will trigger in sync with the remote flash units. This flash is called the local flash and is usually mounted on a camera bracket.

1. Use a flash cable to connect the flash unit's sync terminal to FLASH / PORT 2 of the MultiMAX (set for TRANSMIT mode)
2. Use the **L** key to enable or disable the Local flash

You're all set! Use the camera normally.

- ☞ Using a local flash this way protects the camera from high voltages.
See the **Specifications** section, Page 49, for more information.

STANDARD RADIO OPERATION

Transceiver Control

The MultiMAX operates as either a transmitter or a receiver. To use the MultiMAX as a Transmitter (sending device) set the power switch to TRANSMIT. To use the MultiMAX as a Receiver set the power switch to RECEIVE.

- ☞ There is a special mode that enables a MultiMAX to automatically switch from RECEIVE to TRANSMIT then back to RECEIVE while triggering a remote camera. Read the **Relay Mode** section, Page 39, for more information.

Channels

The MultiMAX is a 32 channel digital radio slave. Each MultiMAX channel represents a digital code transmitted on specific PocketWizard radio frequencies. This enables many photographers to work in the same area. It also enables a photographer to control multiple remote devices (cameras, flash units, etc).

A MultiMAX (set for TRANSMIT mode) will trigger any number of MultiMAX units (set for RECEIVE mode) set to the same channel. Units set to different channels will not interfere with each other.

From the main screen press the ▲▼ keys to change channels.

Some MultiMAX features are only available on higher channels. Refer to the table below for features / channels availability:

Features	Channels 1-16	Channels 17-32
Digital Radio Signal.	X	X
Delay including Rear Curtain Sync	X	X
Intervalometer	X	X
Multipop	X	X
Relay Mode	X	X
Selective Quad-Triggering		X
Confirmation (Radio and Flash)		X
Fast Mode		X
SpeedCycler		X



Compatibility

MultiMAX channels are compatible with all PocketWizard radio slave products per the table below:

Digital Radio Model	MultiMAX Compatible Channels
Older MultiMAX units	1-16 17-32 Quad-Triggering or Fast Mode
PocketWizard 10 Channel Classic	1-10
PocketWizard 16 Channel Classic	1-16
PocketWizard Plus PocketWizard Plus II	1-4
PocketWizard MAX	1-16 17-32 Quad-Triggering or Fast Mode
Sekonic Digital Radio Transmitter Module RT-32 (L358, L608, L608 CINE)	1-16 17-32 Quad-Triggering
Sekonic Digital Radio Receiver RR-4	1-4
Sekonic Digital Radio Receiver RR-32	1-16 17-32 Quad-Triggering or Fast Mode
Calumet Radio Equipped Turbo Filter	1-9
Profoto Flash Packs with built-in PocketWizard Receivers	1 – 16 1 – 32 Quad-Triggering
Norman Flash Packs with built-in PocketWizard Receivers	1 – 16 1 – 32 Quad-Triggering
Dyna-Lite Flash Packs with built-in PocketWizard Receivers	1 – 16 1 – 32 Quad-Triggering
Kodak DCS Pro 14n, DCS Pro 14nx, and DCS Pro SLR/n Digital Cameras with PocketWizard Upgrade	1 – 16 1 – 32 Quad-Triggering
Nikon D1 series with PocketWizard Upgrade	1 – 16 1 – 32 Quad-Triggering

The digital radio design of the MultiMAX will enable it to be fully compatible with future PocketWizard products.

▲ PocketWizard manufactures products for 3 different world frequencies: US, CE, and JAPAN. Not every product is manufactured for every frequency. Products manufactured for one world frequency are **NOT** compatible with products from another. Make sure to order products that are compatible with the frequency you already own, or are legal for use in your world region.


Selective Quad-Trigging (**A B C D** keys)

This powerful feature is used to individually control up to 4 sets of MultiMAX units (set for RECEIVE mode) on the same channel. Each keypad letter, **A B C D** refers to an individual zone. Each zone can be independently selected or deselected from a MultiMAX (set for TRANSMIT mode).


Follow the steps below to test Quad-Trigging:

1. Set one MultiMAX to TRANSMIT mode
2. Set up to 4 MultiMAX units to RECEIVE mode (same channel as TRANSMIT unit)
3. Using the **A B C D L** keys set each RECEIVE unit to a different zone
4. On the TRANSMIT unit use the **A B C D L** keys to select which zones will trigger. The zone is selected when the letter is displayed on the LCD screen. The zone is deselected when a dot appears where the letter would be displayed.
5. Press the **TEST** key on the MultiMAX (set for TRANSMIT mode) unit to trigger the selected zones


Any number of MultiMAX units (set for RECEIVE mode) may be set to the same channel and zone, and will trigger simultaneously. Selective Quad-Trigging is only available on channels 17 and higher.



TRANSMIT unit
Channel: 17
Zones: A, B, and Local



RECEIVE unit
Channel: 17, Zone: A




RECEIVE unit
Channel: 17, Zone: B

Classic Channels

Classic channels are compatible with early PocketWizard models and the PocketWizard Plus. Selective Quad-Triggering is only available in channels 17 through 32. In channels 1 through 16 the display will show CLASSIC CHANNEL and zones **A B C D** do not appear. The **A** key simply toggles the remote receivers on or off and is displayed on the main screen as **R**. It is not possible to toggle both the remote (**A** key) and the local flash (**L** key) off at the same time when using a CLASSIC CHANNEL. Operation on these channels is identical to the function of the LOCAL / BOTH / REMOTE switch found on PocketWizard Plus and Classic Transmitters.

L Key = On any channel the **L** key toggles the local flash on or off in a MultiMAX (set for TRANSMIT mode).


- ☞ See the **Connecting MultiMAX (set for TRANSMIT mode) to Flash** section, Page 16, for more information.
- ☞ The **L** key toggles **Relay Mode** when using a MultiMAX (set for RECEIVE mode). See the **Relay Mode** section, Page 39, for more information.



**TRANSMIT unit set to
CLASSIC CHANNEL 4
Remote and Local selected**

True Confirmation

Because the MultiMAX is a true transceiver it automatically confirms triggering. It can perform this on two levels: it confirms the round trip radio signal and can confirm actual flash sync with an optional flash confirmation cable. It does this for all Quad-Triggering zones on every trigger. Confirmation is indicated visually on the main screen and audibly using beep modes.

 For audible confirmation settings see the **Beep Menu** section, Page 28.

Radio

Radio confirmation is displayed on TRANSMIT units in the **A B C D** area of the LCD. An inverted letter shows an error. A normal letter shows confirmation.

During normal operation the display will show selected and active **A B C D** zones not inverted. Confirmation will occur on every trigger and only in the event of an error will the zone letters invert.

Optional Flash Confirmation Cable


Using the flash confirmation cable the MultiMAX can confirm flash sync for all four zones on every trigger.

1. Attach flash confirmation cable to PORT 1 for each MultiMAX (set for RECEIVE mode)
2. Locate the sensor so that it can only see the flash from the correct flash unit
3. Press the **TEST** button on a MultiMAX (set for TRANSMIT mode) to test flash confirmation. Correct flash confirmation is displayed on the main screen with a flash icon to the right of each zone performing flash confirmation. In the event of an error (either no flash was detected or the radio link was incomplete) the zone letter and the flash icon will invert

A MultiMAX (set for TRANSMIT mode) will look for RECEIVE units and confirm the radio link after each of these operations:

- Every trigger
- Power on or switch from RECEIVE to TRANSMIT
- Channel change
- Zone change (including **L**)
- Exiting the menu system





- Confirmation can only be performed using MultiMAX units on channels 17 and higher. PocketWizard Plus, Classic, and the original MAX do not perform confirmation.
- True Confirmation is designed to work with one MultiMAX (set for RECEIVE mode) per zone. Multiple RECEIVE units set to the same channel and zone will not individually confirm and may cause incorrect confirmation errors. If multiple MultiMAX units (set for RECEIVE mode) on the same channel and zone are a mix of flash and non-flash confirmation units then accurate flash confirmation will not be reported.

The following table shows how confirmation works in different modes:

MultiMAX Mode	Radio and Flash Confirmation
A RECEIVE unit using Selective Quad-Triggering	Provides normal radio and / or flash confirmation
A RECEIVE unit set to a Delay mode	Will not provide confirmation
A RECEIVE unit set to FAST MODE	Confirms on zone A only
A RECEIVE unit set to Intervalometer or Multipop	Provides radio confirmation before the first interval only

Note: Older MAX and MultiMAX units set to FAST MODE will not confirm on any zones.

MENU SYSTEM


Navigation

Many functions of the MultiMAX are accessed through easy-to-navigate menus.

Press ***/MENU** to enter the menu system. Menu items are selected by using the **A B C D L** keys. You can also use the **▲▼** keys to highlight the menu item you want, then press ***/MENU** to select.

While within the menus the ***/MENU** key performs two functions:

- If a menu is displayed, pressing ***/MENU** will select the highlighted item. Use the **☼** key to exit the menus at any time.
- If a numeric entry is displayed, pressing ***/MENU** stores the displayed number in memory and proceeds to either the next input screen or the main screen depending on mode.

 In the next chapters many of the headings will be followed by ***/MENU** and some letter combinations. These are quick references for the keys to press to get to that function fast.

Numeric Entry


Several menu items require a number or value to be entered. Numeric entry is performed with **A B C D** and **▲▼** keys. The **A B C D** keys each select and add 1 to a specific digit as follows:


- A** – selects and adds 1 to the 4th digit from the right
- B** – selects and adds 1 to the 3rd digit from the right
- C** – selects and adds 1 to the 2nd digit from the right
- D** – selects and adds 1 to the rightmost digit


Once a digit has been selected, use the **▲▼** keys to adjust the number. Press and hold **▲▼** for faster entry.

Numbers entered in this fashion are saved when the ***/MENU** key is pressed and will remain saved even after power is turned off. If the unit is powered off while a numeric entry screen is displayed, the displayed number will not be saved.

 **L** can also be used in Numeric Entry. In some cases, **D** and **L** select the same digit.

 To perform a Lag Time Measurement, use **Equalize Mode** (see Page 34) which requires that the MultiMAX be set for **RECEIVE**.

 To quickly get to the lowest setting press and release the **A** key once (selects the highest digit) then press and hold the **▼** key.



Example 1: Numeric Entry



Example 2: Numeric Entry

MAIN MENU

From the main screen press ***/MENU** to enter the Main Menu. The **▲▼** arrow keys can be used to highlight a menu function. Press ***/MENU** to select that function. You can also press the corresponding letter as listed below.

A: Advanced Menu – ***/MENU A**

Press **A** to enter the Advanced Menu. The Advanced Menu contains Delay modes (including Rear Curtain Sync), Intervalometer, Multipop, and SpeedCycler modes.



Main Menu
Go Advanced

B: Basic Settings – ***/MENU B**

Press **B** to enter the Basic Settings menu. It contains Contact time and Beep menu.

C: Counter Menu – ***/MENU C**

Press **C** to enter the Trigger Counter Menu which contains Counter direction, and other counter functions: Reset / Clear, Disable, and Load.

D: Go Advanced – ***/MENU D**

D: Go Normal – ***/MENU D**

Press **D** to toggle between the last Advanced mode used and Normal mode.

This function enables a quick return to standard or normal operation from an advanced function. The settings of the advanced function are saved.



Main Menu
Go Normal

- 📌 Go Normal is a quick way to get to standard radio slave operation after using advanced functions and menus. Use this function to “turn off” an advanced mode and use the MultiMAX as a radio slave only.

BASIC SETTINGS

Press ***MENU B** to enter the Basic Settings menu. Press the corresponding letter for the setting you wish to adjust.

A: Contact Time – *MENU B A


Contact time is the length of time that CAMERA / PORT 1 or FLASH /PORT 2 outputs remain contacted. The default Contact Time of 0.08 is enough to trigger most camera motor drives and flashes. Many photographers will never need to adjust this number.

👁 Contact time is how long the internal switch is held closed. For example, if the contact time is set to 3 seconds and a camera motor drive is attached to a MultiMAX, when the MultiMAX triggers the camera it will hold the contact for 3 seconds. This is identical to pressing and holding the camera's trigger button for 3 seconds. The contact time starts as soon as any input is complete. Input can be from any of the following sources: **TEST** button is pressed, hot shoe is triggered, or radio trigger is received. Additional triggers occurring during contact time are ignored.

👁 Contact time is NOT the length of time a MultiMAX (set for TRANSMIT mode) will send a radio triggering signal. Contact time affects PORT 1 and PORT 2 only and does not affect radio trigger transmission. Pressing and holding **TEST** on a MultiMAX (set for TRANSMIT mode) will continuously send the radio trigger signal and hold the contact on a MultiMAX (set for RECEIVE) as well as the TRANSMIT unit. When the **TEST** button is released each unit's contact time will then begin.



Basic Settings Menu



Set Contact Time Screen

0.08 seconds can theoretically accommodate shooting with remote flash up to 12 FPS (Frames Per Second), however testing with your specific equipment may be required. Setting the Contact Time to 0.01 seconds will work with most cameras and flashes, and offers the fastest FPS (up to 30) with some PocketWizard products.

For more information about maximum frame rates and optimum settings, please visit the User Forum of our website at: www.pocketwizard.com

For triggering remote cameras, a longer contact time allows for continuous repeatable motor drive triggering (example: 5 frame bursts every trigger). It also allows for controlled bulb exposure.

- **Example of Burst Shooting:** If a remote camera is capable of firing 3 frames per second in continuous motor drive, then a contact time of 1 second will always result in this remote camera triggering for 3 exposures
- **Example of Bulb / Shutter Held Open:** Set the contact time for the desired bulb exposure time and set the camera to bulb or B mode. When triggered the shutter will remain open for the contact time

For triggering a remote flash contact time can act as a flash recycle lockout.

- **Example of Flash Recycle Lockout:** To guarantee that a flash cannot be triggered faster than its recycle time, set the contact time to be just longer than the recycle time

☞ This method of flash recycle lockout does not work with all flash systems as some will not recycle while the sync contact is held. See **Recycle Lockout** in the **Applications of Advanced Functions** section, Page 41, for another recycle lockout method.

☞ If you are using **Intervalometer** or **Multipop** modes, read these sections, Page 36 and Page 37, for information on these modes and how they interact with Contact Time.

B: Beep Menu – */MENU B B

This menu controls the beep functions of a MultiMAX. Press the corresponding letter to set the desired function of the built-in speaker.

A: Beep on All – */MENU B B A

MultiMAX will beep on all triggering, confirmation errors, and zero counts as indicated below as well as on any key pressed.

B: Beep on Trigger – */MENU B B B

Beep on Trigger performs the same beeps as Beep On All minus the double beep when the Counter hits zero in Count Down, Multipop, or Intervalometer modes. Unit will beep when triggered by **TEST** button, PORT 1, a Radio Trigger, or the Hot Shoe per the table.




Beep Menu

Beep Characteristic	Indicates
Single Short Beep	Indicates Proper Confirmation
Single Long Beep	Indicates Trigger Error
Single Very Short Beep	When any Key is pressed

C: Beep on Zero / Error – */MENU B B C

The MultiMAX unit will not beep on normal triggering. The MultiMAX will beep only when the counter reaches zero and on confirmation errors in the following manner:

Beep Characteristic	Indicates
Single Long Beep	Indicates Trigger Confirmation error or remote MultiMAX (unit set for RECEIVE mode) has reached zero count
Double Long Beep	Indicates MultiMAX has reached zero count
Single Short Beep	Any Key is pressed except TEST

 A MultiMAX (set for RECEIVE mode) set to Beep on Zero / Error or set to Beep on All will indicate a confirmation error if the unit is also set to count down and the counter reaches zero. See the Counter section, Page 30, for more information.

D: Beep Disable – */MENU B B D

Turns off all beep functions. Unit will not beep.

C: LCD Contrast Adjustment – */MENU B C

Enters the LCD Contrast Adjustment screen. Use ▲▼ to adjust the contrast. Contrast can be affected by temperature. Setting the contrast to a middle setting is recommended for most situations.

D: RESET - */MENU B D

Resets the unit to factory defaults. CLEAR/RESET is performed as if you held **C** on power up (see Page 52 for more information on Factory Defaults). You will be asked to Press **C** to confirm. Pressing any other key (except **TEST**) will cancel the reset operation.



COUNTER MENU

Press ***/MENU C** enter the Counter Menu. This menu controls the counter functions of the MultiMAX. The counter can show the total number of triggers. Count is incremented on every trigger from any source: PORT 1, **TEST** button, Hot Shoe, or Radio Trigger.

A: Count Up + Reset – ***/MENU C A**

Count is set to COUNT UP (example: 0,1,2,3,...) and the counter is reset to 0. The main screen will display COUNT ↑: 0.

B: Count Down + Reset – ***/MENU C B**

Count direction is set to DOWN (example: 10,9,8,7,...), you are prompted to enter a count, then the counter is reset. The main screen will display COUNT R: XXXX

 The count down function could be used to indicate the number of remaining frames for a remote camera.


C: Clear / Reset – ***/MENU C C**

Count direction is not changed. Counter is reset to 0 if count direction is set to up, or the counter is reset to the load value if count direction is set to down. If the counter is disabled, then this function will enable the counter using the last count direction set. The Counter is cleared and reset in this fashion when the unit is powered down.


 Use *** C C** as an easy to remember quick key combination for fast counter reset.

D: Disable – ***/MENU C D**

Counter is disabled and is not displayed on the main screen. While disabled the counter does not count.



Counter Menu



TRANSMIT unit set to
Count Up




Load Counter Screen

ADVANCED MENU

Press ***/MENU A** to enter the Advanced Menu. This menu contains the advanced functions of the MultiMAX.

Precision timing and sequencing operations are available in this menu.


-  Press ***/MENU D** to cancel advanced functions and return to normal mode. See the section on **D:Go Advanced** and **D:Go Normal**, Page 25.





RECEIVE unit
Advanced Menu

A: Delay Menu – TRANSMITTER – ***/MENU A A**

Enters the delay menu for MultiMAX units (set for TRANSMIT mode).

-  Delay menus, with the exception of Rear Curtain, require numeric entry. See the Numeric Entry section, Page 24.

-  All delay screens (numeric entry or rear curtain) are instantly active and triggering can occur while these screens are displayed. A value displayed on these screens will be used immediately on trigger. This is useful for fine tuning a delay or adjusting rear curtain sync.

-  The maximum delay is 9.9999 seconds. For longer delays see the Intervalometer section, Page 35.




TRANSMIT unit
Advanced Menu

A: Remotes + PORT 2 – ***/MENU A A A**

Enters the numeric entry screen. Delays the remote units and PORT 2. Remote units and PORT 2 will fire at the same time after the displayed delay. PORT 2 will remain contacted for the set contact time. On the main display a small letter **D** will appear over the right of the large **L** to show that the Local output (PORT 2) will be delayed. Pressing **L** will toggle the Local output (PORT 2) on and off, but the small **D** will remain.



TRANSMIT unit
Delay Menu



TRANSMIT unit
Remotes + PORT 2 delayed


B: Remotes Only – */MENU A A B

Enters the numeric entry screen. Delays the Radio remote units only. PORT 2 will trigger immediately. Remote units will trigger after the displayed delay. If the contact time for the MultiMAX (set for TRANSMIT mode) is longer than the delay, PORT 2 will remain contacted for the delay time rather than the contact time.

C: Rear Curtain – */MENU A A C


Enters the Rear Curtain screen. Use this mode to trigger the flash at the end of an exposure rather than at the beginning. In this mode both the Radio remote trigger and PORT 2 are delayed.

Use the ▲▼ keys to set the rear curtain sync time equal to the camera's shutter speed. Common rear curtain sync times are available per the table below:




Rear Curtain Screen

Rear Curtain Sync Time	Decimal Equivalent	Actual Delay Used
1/1	1 second	0.98 seconds
1/2	0.5 seconds	0.49 seconds
1/4	0.25 seconds	0.24 seconds
1/8	0.125 seconds	0.119 seconds
1/15	0.0667 seconds	0.062 seconds
1/30	0.0333 seconds	0.029 seconds
1/60	0.0167 seconds	0.014 seconds

 For rear curtain sync times other than the ones displayed above, or for fine tuning rear curtain times for your specific equipment, press ***/MENU** to return to the main screen. Press ***/MENU A A A** (see the section **A:Delay Remotes + PORT 2**, Page 31) and adjust the delay number as needed.

A: Delay Menu - RECEIVER – */MENU A A

Enters the delay menu for a MultiMAX (set for RECEIVE mode). Each RECEIVE unit can have its own delay for sequences or for synchronization. To easily delay all RECEIVE units the same amount, use the Transmitter's delay.

 RECEIVE units set to delay do not perform confirmation.


A: PORT 1 + PORT 2 – */MENU A A A

Enters the numeric entry screen. PORT 1 and PORT 2 are delayed the same amount and trigger simultaneously after the set delay time. Both ports remain contacted for the set contact time. Triggers can come from either the **TEST** key or a radio trigger from any PocketWizard Transmitter. On the main display a small letter **D** will appear to denote that PORT 2 will be delayed.


 Pressing **L** will toggle **Relay Mode** on and off but PORT 2 will still trigger after the set delay. See the **Relay Mode** section, Page 39, for more information.

B: PORT 2 – */MENU A A B

Enters the numeric entry screen. PORT 1 triggers immediately upon pressing **TEST** key or Radio Trigger. PORT 1 contact is held for the set delay time. PORT 2 triggers after the set delay time and contact is held for the set contact time.



RECEIVE unit
Delay Menu



RECEIVE unit
PORT 1 + PORT 2 delayed

C: Equalize – */MENU A A C

Equalize Mode is a specialized delay mode for synchronizing multiple cameras to one flash. This mode is designed to work with shutter speeds up to 1/125 on some cameras, but there are many factors that could affect operation.

This is the only place where Lag Times can be measured.

 Read the **Camera Equalization** section, Page 42, before continuing.

Equalize mode is designed to be used with at least 3 MultiMAX units (set in RECEIVE mode). Two or more MultiMAX units will be attached to cameras and one MultiMAX will be attached to a flash unit. A MultiMAX or other PocketWizard TRANSMITTER will be used to trigger the system.


1. Place a MultiMAX (set to RECEIVE mode) on the camera hot shoe or attach cable from camera's PC terminal to PORT 1
2. Attach cable from PORT 2 to camera's motor drive. If available, use a Pre-Trigger cable (more information in the **Camera Equalization** section).
3. If the Equalize Screen is not displayed then press ***/MENU A A C** from the main screen to enter Equalize Mode. This enters the numeric entry screen and 0.1500 seconds are displayed
4. Press the **TEST** key. The camera should trigger and a lag time (camera triggering delay) will be measured and displayed. Press **TEST** every few seconds for 5 to 15 exposures until you see the fastest lag time (lowest number displayed) for the camera
5. Press the ***/MENU** key to return to the main screen. A delay value will be displayed. This number is a calculated number and will differ from the lag time you saw on the previous screen
6. Repeat steps 1 through 5 for each camera to be equalized. Use one MultiMAX (set for RECEIVE mode) per camera.
7. Attach a MultiMAX (set for RECEIVE mode) to a flash unit.
8. From the main screen press ***/MENU A A C**. When the numeric entry screen appears with 0.1500 displayed, simply press ***/MENU** to return to the main screen. Do not adjust the number and do NOT press **TEST**. The main screen will show a delay of 0.1500
9. Press **TEST** on any PocketWizard Transmitter to trigger this equalized system

B: Intervalometer (Time Lapse Photography) – */MENU A B

Enters the Intervalometer interval setting screen.

Intervalometer can be used to trigger a flash or a camera at a set interval (time gap between triggers) for a set number of triggers. The interval time is set in **HH:MM:SS** format (Hours:Minutes:Seconds) up to a maximum of 99:59:59.

While Intervalometer is running, it will display a count down time until the next trigger on the main screen. Also, TRIG will be displayed on the main screen in inverse video as the PORTs are being triggered.





Intervalometer Mode
Set Interval Screen

1. From the main screen press ***/MENU A B** to enter the numeric entry screen
2. Enter the interval or time gap between triggers
3. Press ***/MENU** to proceed to the next screen
4. Enter the count or number of triggers
5. Press ***/MENU** to return to the main screen. The interval will be displayed, and the count will show the number of triggers to be executed.
6. Press **TEST** or trigger MultiMAX via Radio to begin intervalometer function

Intervalometer has two modes of operation depending on which PORT is used:

- **PORT 1** = first trigger takes place **AFTER** first interval
- **PORT 2** = first trigger takes place **BEFORE** first interval





 A MultiMAX (set for TRANSMIT mode) does not send interval radio triggers. The MultiMAX (set for TRANSMIT mode) will send out a single radio trigger pulse at the beginning of the first interval only. It will continue to trigger devices attached to its PORTs, but it will not send a radio trigger for any more intervals. For remote interval operation, use interval mode on a RECEIVE unit. Each MultiMAX (set for RECEIVE mode) may have a unique interval setting or can be used with equal settings. Interval and count entry screens are instantly active



TRANSMIT unit
120 second Interval
36 trigger Count

The Set Interval and Adjust Counter screens are instantly active. While the Set Interval screen is displayed a change of interval will be immediately executed upon trigger either from the **TEST** key or Radio trigger. The count used will be the last count set. If the Adjust Counter screen is displayed a change of count will be immediately executed upon trigger using the last interval set.

 Intervalometer can be interrupted by pressing and holding the ***/MENU** key.


-  For delays longer than 9.9999 seconds (maximum available in delay modes) use Intervalometer or Multipop mode. Set the interval to the desired delay. Set the count to 1. Attach your camera to PORT 1 and trigger the MultiMAX . The camera will trigger after the set interval.
-  Contact time is affected by Intervalometer mode. If you set an interval that is LESS than the contact time, the contact time becomes the interval minus 0.3 seconds. If you set an interval that is GREATER than the contact time, the contact time is simply performed as entered.
-  When using Intervalometer and Relay Mode together, a MultiMAX (set for RECEIVE mode) will switch to Transmit mode and send a Radio trigger after the last interval. See the **Relay Mode** section, Page 39, for more information.
-  When using Intervalometer or Multipop modes exclusively, battery life can be 200-300 hours. See the **Reset to Default Factory Settings** section, Page 52, for more information.

C: Multipop – */MENU A C


Enters the Multipop interval setting screen. This mode is for triggering a flash multiple times from one trigger. It can be used during one long exposure to increase depth of field or for special effect sequencing. The interval setting is normally used to set a safe flash recycling time, while the count is set to the number of flashes or “pops” desired.

Multipop is identical in function to Intervalometer with one exception: the multipop interval range has finer resolution; from 0.01 to 999.99 seconds in 0.01 (1/100) second increments. This allows for finer control when setting flash recycle time. This mode can be used for cameras or flash units.

1. From the main screen press ***/MENU A C** to enter the numeric entry screen
2. Enter the interval or time gap between triggers
3. Press ***/MENU** to proceed to the next screen
4. Enter the count or number of triggers
5. Press ***/MENU** to return to the main screen. The interval will be displayed, and the count will show the number of triggers to be executed
6. Press the **TEST** key or trigger the MultiMAX via Radio to begin Multipop function




**Multi-pop Mode
Set Interval Screen**



**TRANSMIT Unit
5.00 second Multi-pop Interval
10 trigger Count**

The following chart is a starting point for calculating how the number of flashes or pops affects F-stops. Since every flash unit is different, use a light meter or other method for more precise calculations.

Number of Pops	Stops	Number of Pops	Stops
1	Add 0 stops	6	Add 2.5 stops
2	Add 1 stop	7	Add 3 stops
3	Add 1.5 stops	8	Add 3.5 stops
4	Add 2 stops	9	Add 4 stops


 Contact time is affected by Multipop mode. If the contact time is set greater than the Multipop interval, the contact time will automatically be set to interval time MINUS 0.01 seconds. This means that a remote camera or flash will remain triggered with only a 1/100 second release between contacts. This short released time may not be long enough to re-trigger some cameras or flash units. If this is the case, set the contact time lower.

D: SpeedCycler - TRANSMITTER – ***MENU A D**

Enables SpeedCycler mode. Use this mode to rapidly cycle through remote flash units and trigger faster than a single flash can recycle by using multiple flash units. It can also be used for triggering remote cameras sequentially.

This mode only works with Quad Triggering channels (17 and higher) and two or more MAX or MultiMAX units (set for RECEIVE mode).


1. From the main screen press ***MENU A D** to enable SpeedCycler mode on a MultiMAX (set for TRANSMIT mode)
2. Enable two or more remote zones
3. Set each MultiMAX (set for RECEIVE mode) to a different zone
4. Trigger the MultiMAX (set for TRANSMIT mode). The first trigger will fire the first zone selected, the second trigger will fire the next zone selected. The display indicates the next zone to trigger with an arrow. Only the zone just triggered will display proper confirmation



TRANSMIT unit
SpeedCycler Mode

A = triggered with flash
confirmation


B = next zone to be triggered

 If **L** is selected then PORT 2 on the MultiMAX (set for TRANSMIT mode) will trigger every time and is not cycled. It will be in sync with each cycled zone.



D: Fast Mode - RECEIVER – */MENU A D

The MultiMAX is designed to sync cameras and flash units at shutters speeds up to 1/250th for most focal plane shutters (35mm) and 1/500th for most leaf shutters. Some camera and flash combinations are capable of fast sync speeds up to 1/1000th. The MultiMAX (set for RECEIVE mode) is capable of operation at these speeds in **Fast Mode**. Check your camera's and flash unit's manuals for the maximum sync speeds allowed by your equipment.



RECEIVE unit Fast Mode

A MultiMAX (set for RECEIVE mode) in fast mode will show FAST MODE on the display. While in this mode Quad-Triggering and Relay Mode are not available and the **A B C D L** keys perform no function on a RECEIVE unit. A MultiMAX (set for TRANSMIT mode) will trigger RECEIVE units in FAST MODE with any remote zone selected, but will perform confirmation only on zone **A**.

OTHER FEATURES

Keypad Lock – Hold 🔒

This function prevents inadvertent key presses. Press and hold the 🔒 key for 3 seconds to toggle keypad lock on or off.

All keys are locked except 🔒 and **TEST**.

While the keypad is locked pressing any of the keys, **A B C D L ▲ ▼** or */MENU will display the message "KEYPAD LOCKED."

High Voltage Protection

Many electronic cameras can be damaged by high flash sync voltage. Refer to your camera's manual for more information. The MultiMAX protects the camera from high flash sync voltage. The MultiMAX can accept up to 250 volts, but there is only a safe 3.1 volts present at the hot shoe or PORT 1. A camera triggering a MultiMAX (set for TRANSMIT mode) via the hot shoe or PORT 1 only encounters 3.1 volts. This voltage is not MultiMAX battery dependent and will not vary over the life of the batteries.

👉 See the **Hot Shoe Note** in the **Specifications** section, Page 50, for more information.

USB Port


The **MultiMAX** includes a USB connector that is intended for future firmware upgrades. Any available upgrades will appear on the **PocketWizard** Web site www.pocketwizard.com, and can be downloaded with a USB connecting cable (not included). Complete instructions will be published on the website in the near future.

Please Note: The MultiMax is not configured as portable storage device; do not attempt to power another USB device with the MultiMax. The MultiMAX cannot be powered via the USB port.



Relay Mode (RECEIVE Mode Only) – L

In this mode a remote camera's motor drive is triggered by a MultiMAX (set for RECEIVE mode). The MultiMAX then switches to TRANSMIT mode and waits for a sync pulse from the camera. Upon getting the sync pulse from the camera the unit then triggers remote flash units via radio and returns to RECEIVE mode, ready to trigger the camera again. Using this mode it is possible, using only 3 PocketWizard units, to have complete wireless triggering.



**RECEIVE unit in Relay Mode
Receives Channel 22, Zone A
Transmits Channel 20**

1. Set a MultiMAX to TRANSMIT mode and select the channel and zones for the remote flash units
2. Set the same MultiMAX to RECEIVE mode and select the channel and zone for the remote camera. Use a different channel than the remote flash units.
3. Press **L** to toggle Relay Mode on. The screen will display RLY XX (where XX is the TRANSMIT channel to be used for relay)
4. Connect the camera's PC terminal to PORT 1 or attach the MultiMAX to the camera's hot shoe
5. Connect the camera's motor drive to PORT 2
6. Trigger the MultiMAX via radio trigger. The camera's motor drive will trigger and the MultiMAX display will change to TRANSMIT mode. The MultiMAX will wait 1.5 seconds for a trigger from the camera. If it gets a trigger in that time it will trigger the remote flash units and return to RECEIVE mode. If it does not get a trigger in that time it will return to RECEIVE mode without triggering the remote units.

Software Version Display – Hold **A** on power up

To check the software version of the MultiMAX without resetting the unit to factory defaults, perform the following

1. Set power switch to OFF
2. Press and hold **A** key
3. Continue to hold **A** and set the power switch to either RECEIVE or TRANSMIT
4. Release **A** key when software version appears
5. Use unit normally

 See the **Reset to Default Factory Settings** section, Page 52, for more information.

APPLICATIONS OF ADVANCED FUNCTIONS

The applications below are unique ways to use the advanced functions of the MultiMAX. Many of them require fine-tuning or adjustment to work with different camera equipment. Always perform test exposures to insure reliable results.

Self-Timer or Cable Release

Delays, or Intervalometer and Multipop with a count of 1, can be used as a camera timer for self portraits or as a trigger delay to reduce camera shake. Review **Delay**, **Intervalometer** and **Multipop** sections for more information.

TTL / Auto flash Helper

When using an on-camera TTL flash or Automatic exposure flash with a remote flash there may be situations where you do not want the remote flash to affect the TTL or Auto flash sensor. The on-camera flash can underexpose by quenching early (turning off too soon) because it measured the light from the remote flash. The reverse of this can also be undesirable. If the remote flash is in Automatic mode, it may quench too early because it sensed the light from the on camera flash.


Using Delay mode can help solve this problem. Follow the steps below if using a TTL or Automatic flash attached directly to the camera:

1. Attach the camera's PC terminal to PORT 1 on a MultiMAX (set for TRANSMIT mode)
2. Attach manual or Automatic flash to MultiMAX (set for RECEIVE mode)
3. On the MultiMAX (set for TRANSMIT mode) press *** / MENU A A B** to enter the set delay screen
4. Enter in a delay of 0.0020 (1/500)
5. Trigger the camera normally

The on-camera flash will trigger immediately and have enough time to complete its full exposure. After the set delay time the remote flash will trigger. This operation is dependent on camera sync speed and flash duration. The delay time of 0.0020 (1/500) will work with a focal plane shutter (35mm camera) at 1/125 shutter speed and a flash duration not longer than 1/400.



Use the formula below to help calculate your maximum safe shutter speed based on your flash durations.

 Refer to the **Time Conversion Charts** section, Page 54, to convert fractions into decimals for the formula.

1. Add your maximum (longest) flash durations together (decimals, not fractions)
2. Add another 0.002 (focal plane) or 0.001 (leaf shutter) to compensate for shutter travel time
3. On the **Shutter Speed Conversion** chart find the next highest decimal number in the chart. The corresponding shutter speed is the fastest speed you can safely use for this procedure
4. Set the delay time on the MultiMAX (set for TRANSMIT mode) to the same number as your on-camera flash unit's longest flash duration

Programmed Sequence Shooting

Traveling stroboscopic effects can be achieved by using multiple MultiMAX units (set for RECEIVE mode) in delay mode. Set each RECEIVE unit to a different delay and trigger from a PocketWizard. The sequence is identical on repeat triggers.

Recycle Lockout

Some flash units can be damaged if they are triggered too quickly or before they are fully recharged. This may cause the flash to overheat. Use Multipop Mode to protect the flash by setting a safe recycle lockout time. Follow the steps below:

1. On a MultiMAX (set for RECEIVE mode) press ***/MENU A C**
2. Enter the desired recycle lockout time and press ***/MENU**
3. Enter a count of 1 and press ***/MENU**
4. Attach remote flash to PORT 2

Example: If the lockout time you entered was 3 seconds, then the remote flash could not be triggered more than once every 3 seconds.



Camera Equalization

Equalization, or synchronizing multiple cameras to the same flash, requires precision timing. Even though we perceive camera triggering activity as instantaneous, it is not. Even the flash, which appears to provide light only for an instant, has a time duration (flash duration) that needs to be factored into synchronization calculations.

Every camera has a delay from the time it is triggered until the shutter is fully open. The trigger can originate from either the camera's trigger button or via the motor drive port. This delay is called lag time and it can be different from camera to camera and may even vary between two cameras of the exact same model. If two cameras are triggered at exactly the same time their shutters will be open at different moments. If one camera is attached to a flash, the other camera's shutter will probably not be open at the right moment to capture the flash.

Some cameras are not suitable for equalization. For best equalization a camera must have a consistent lag time. If a camera's lag time varies widely or unpredictably from shot to shot then it may not be possible to synchronize that camera. This is not a flaw of either the camera or the MultiMAX. A varying lag time in a camera is considered acceptable operation for the majority of photographic situations. Cameras are usually designed to respond predictably shot to shot, but are not necessarily or specifically designed to do so with the precision needed for equalization. Many factors can affect a camera's lag time:

- **Camera Pre-Trigger status** – cameras that have a two stage trigger button (half press “wakes up” the camera, full press triggers the camera) will probably have widely different lag times if triggered while awake versus asleep. Cameras usually have more consistent lag times if they are kept “awake” or Pre- Triggered. The camera will also respond more quickly, but will consume batteries at a faster rate. Pre-Trigger cables are available from PocketWizard for many cameras
- **Camera batteries** – lag times may begin to drift or slow down as the camera's batteries fade, especially in primarily mechanical cameras. Fresh batteries are recommended for equalization
- **Temperature and humidity** – as these factors change, the mechanical parts of a camera may move differently thus affecting lag time. A temperature increase may decrease lag time as the camera's internal lubricants are warmed and flow more freely or vice versa
- **Horizontal vs vertical orientation** – as a camera is moved through these orientations various mechanisms, especially shutters in focal plane cameras, will be affected by gravity making them move differently thus affecting lag time. In general, do not change a camera's orientation during equalization

- **Multiple mechanical systems** – cameras that have many changeable mechanically interacting parts (film backs, motor drives, lens shutters) are likely to have different lag times with different hardware combinations. A leaf shutter is in the lens so changing lenses on a leaf shutter camera will change lag time. In some medium format cameras having the film back loaded versus unloaded can make a significant difference. For consistent results always use the same components (lens, body, and film back combination for example) each time
- **Auto-focus and exposure computers** – some auto-focus and exposure systems will introduce widely varying lag times as lens travel and exposure calculations can take unpredictable amounts of time. An electronic camera set to full manual generally provides the most consistent lag times


Lag Time Measurement – *** /MENU A A C L** (RECEIVE units only)

The first step to camera synchronization or equalization is measuring a camera's lag time (triggering delay). The MultiMAX can measure a camera's lag time in most delay modes. Knowing your camera's lag time is critical for camera equalization, but can also be useful in special effects, industrial, commercial, or other photography that requires critical trigger timing.

Using the information above set up your camera for best equalization performance. Attach a MultiMAX (set for RECEIVE mode) to the camera as follows:


1. Place a MultiMAX in the camera's hot shoe or attach a cable from the camera's PC terminal to PORT 1
2. Attach the cable from PORT 2 to the camera's motor drive. If available, use a Pre-Release cable
3. Press *** /MENU A A C** for a standard delay mode where lag times can be measured
4. The screen should display "Set Delay Using **A B C D L ▲ ▼** " and show a numeric value. Press **TEST**. The unit will trigger the camera and time the delay until a sync pulse is sensed from the hot shoe or lens
5. Press **TEST** every few seconds to find the fastest and slowest lag times for the camera. Usually the first press of **TEST** will yield a very different number from later measurements. Ignore the first reading. 5 to 15 lag time measurements after the first one should yield consistent results and give a gauge of the fastest and slowest times
6. Using steps 1 through 5, measure and record the fastest and slowest lag times for each camera you wish to equalize. Subtract the fastest from the slowest and record this number as the camera's lag time variation



 Speed is not the most important factor in camera equalization, consistency is. If a slow camera has extremely consistent lag times it will be a better equalization candidate than a faster but inconsistent camera. The reason why it is important to know the approximate fastest lag time for a camera, especially an inconsistent one, is to calculate margin of error (discussed later in this section).

The amount of drift or lag time inconsistency determines the highest shutter speed at which a camera will reliably equalize. The following table should be used as a starting point for testing purposes only. The numbers in this table are based on a 1/1000th or faster flash duration.

Shutter Speed	Probable maximum safe lag time variation for average focal plane (35mm) camera	Probable maximum safe lag time variation for average leaf shutter camera, F:8.0
1/300	≤ 0.0003	≤ 0.0013
1/250	≤ 0.0010	≤ 0.0020
1/200	≤ 0.0020	≤ 0.0030
1/180	≤ 0.0025	≤ 0.0035
1/125	≤ 0.0050	≤ 0.0060
1/90	≤ 0.0080	≤ 0.0090
1/60	≤ 0.0137	≤ 0.0147
1/30	≤ 0.0303	≤ 0.0313
1/15	≤ 0.0637	≤ 0.0647
1/8	≤ 0.1220	≤ 0.1230
1/4	≤ 0.2470	≤ 0.2480
1/2	≤ 0.4970	≤ 0.4980
1	≤ 0.9970	≤ 0.9980
2	≤ 1.9970	≤ 1.9980

 Leaf shutters have different shutter blade travel times depending on aperture. A wider aperture takes longer and reduces the amount of variance allowed. A smaller aperture takes less time thereby increasing the allowable variance. (A leaf shutter set to F:4.0, for example, may reduce the variance to the same as a focal plane camera).

👁 If your camera's maximum sync speed is slower than the number listed then you must use the slower sync speed. Camera equalization does not give a camera faster sync speeds than the camera is designed to handle.

For all shutters it can be assumed that a camera with faster external flash sync speeds (X sync) will have faster shutter travel than cameras with slower X sync speeds. Faster shutter travel times increase the allowable variance. The table above is based on the following shutter travel times:

- Focal Plane (35mm) – 1/1000 (0.0010) to open, 1/1000 to close
- Leaf shutter at f: 8.0 – 1/2000 (0.0005) to open, 1/2000 to close

If a flash is generating light while the shutter is moving then you will see the shutter in the exposure for focal plane shutters. You will see a loss in F stop exposure using a leaf shutter if the flash is generating light as the shutter aperture opens or closes.

A variable flash duration will also affect these calculations. A slow flash is visible for longer and more likely to affect exposure while the shutter is in motion. A short flash duration reduces the likelihood of timing variances affecting the exposure.

It is difficult to measure a shutter's travel time or a flash units duration and it usually requires extremely expensive test equipment. Some electronic flash manufacturers print their flash durations in their manual. The best method for understanding your equipment's equalization capabilities is to shoot many test exposures over a range of settings.

Recommend Equipment for the best results

- Consistent lag time cameras
- Cameras with fast sync speeds
- Electronic flash equipment with short flash duration

One Unit Equalization

To equalize two cameras and one flash at 1/125 with one MultiMAX, follow these steps:

1. Set the MultiMAX to RECEIVE mode
2. Measure lag times of cameras as described and record the fastest lag for each
3. Determine which camera is faster and which is slower overall
4. Determine the delay time
 - a. If the slow camera is more consistent use this formula:
i. Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time
MINUS 0.0025 {calculated safety margin}
 - b. If the fast camera is more consistent use this formula:
i. Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time
PLUS 0.0025 {calculated safety margin}
5. Press ***/MENU A A B** then enter the calculated delay time from Step 4
6. Attach the slower camera's motor drive to PORT 1
7. Attach the faster camera's motor drive to PORT 2
8. Attach the flash to the more consistent (smallest lag time variance) camera
9. Trigger the RECEIVE unit either from the **TEST** key or from a TRANSMIT unit

Two Unit Equalization


Two Unit Equalization is basically the same as above, but allows the two cameras to be more remote. The difference in calculations compensates for radio trigger delay.

1. Set one MultiMAX to RECEIVE mode, and one to TRANSMIT mode
2. Using the RECEIVE unit, measure the lag times of each camera as described above and record the fastest lag for each
3. Determine which camera is faster and which is slower overall
4. Determine the delay time
 - a. *If the slow camera is more consistent use this formula:* Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time **MINUS** 0.0030 {calculated safety margin}
 - b. *If the fast camera is more consistent use this formula:* Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time **PLUS** 0.0020 {calculated safety margin}
5. On the RECEIVE unit press ***/MENU A A A**. Enter the time from Step 4
6. Attach the slower camera's motor drive to PORT 2 on the TRANSMIT unit. Do not leave the MultiMAX (set for TRANSMIT mode) in the hot shoe or have the PC terminal attached to PORT 1 as this may cause a looping or lock-up situation
7. Attach the faster camera's motor drive to either PORT on the RECEIVE unit
8. Attach the flash to the more consistent (smallest lag time variance) camera
9. Trigger the system from the TRANSMIT unit's **TEST** key



If using both MultiMAX units as RECEIVE units being triggered by any PocketWizard Transmitter follow these steps:

1. Set both units to RECEIVE mode
2. Measure lag times of cameras as previously described and record the fastest lag for each
3. Determine which camera is faster and which is slower overall
4. Determine the delay time
 - a. If the slow camera is more consistent use this formula:
 - i. Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time **MINUS** 0.0025 {calculated safety margin}
 - b. If the fast camera is more consistent use this formula:
 - i. Slower Camera's Fastest Lag Time MINUS Faster Camera's Fastest Lag Time **PLUS** 0.0025 {calculated safety margin}
5. Attach the slower camera's motor drive to either PORT on the first unit
6. Attach the faster camera's motor drive to either PORT on the second unit
7. On the second unit press ***MENU A A A**, then enter the calculated delay time from Step 4
8. Make sure there is no delay being performed on the first unit
9. Attach the flash to the more consistent (smallest lag time variance) camera
10. Trigger the system from a TRANSMIT unit's **TEST** key

 If using 4 or more units you may find it easier to use the built-in Equalize mode. See the **Equalize** section, Page 34, for more information.

Equalization Adjustments

With all the variable factors above it may seem that performing the math necessary for equalization is daunting. Here are some techniques for fine-tuning or adjusting equalization times without using specific math:

On some 35mm cameras you can gauge timing without using film. If your camera allows triggering with the film back open you can verify synchronization visually.

1. Perform the steps above to get basic equalization started
2. Point the flash at a blank wall
3. On the camera NOT attached to the flash, set the shutter speed to 1/60
4. Open that camera's back
5. Point the camera at the same wall as the flash
6. As the camera and flash are being triggered look through the shutter plane through the lens at the light from the flash hitting the wall. **CAUTION: MAKE SURE** the flash is set to a comfortable level for your eyes!
7. Note the shape of the light burst. If it is a perfect bright circle then the camera is in sync. If the circle is dark or has a hard line running along one edge then the camera is not in sync. The hard line is the shutter in motion while the flash is still generating light
8. Adjust the shutter speed up or down until you see a perfect circle

📌 The delay time setting screen is instantly active. While in numeric entry mode you can adjust the delay up or down and the displayed value will be executed on the next trigger. Using the “through-the-back” method above or by shooting film, Polaroid, or digital you can adjust the delay and view the results to more suit your specific camera's timings.

The mathematical formulas used thus far are designed for equalizing at 1/125. The final offset number (0.0025 for example) may need to be adjusted when attempting to equalize at faster shutter speeds or slower ones with wide lag variation cameras. The offset number tries to move the flash burst to the middle of the exposure to compensate for drifting lag time. Experiment with different offsets to fine tune your shutter speed, flash duration, and camera timing combinations. Too long or short of an offset and you limit a camera's ability to get the exposure if the lag drifts, even by a small amount.

📌 Visit www.pocketwizard.com for more information on camera specific equalization techniques. As more information becomes available it will be posted there.



TECHNICAL INFORMATION

Specifications

Weight:	5.4 ounces with alkaline batteries
Dimensions:	1.4 inches deep x 2.1 inches wide x 4.0 inches tall (body only) Flexible antenna = 2.4 inches tall. 0.3 inches in diameter
Batteries:	2 x AA (IEC:LR6), 1.5 V batteries, alkaline recommended Read the Getting Started section, Page 13, for more information
ACC (Accessory Port):	For triggering remote motor drive cameras using a PocketWizard ACC Cable
USB Port:	For connecting your MultiMAX to a computer for firmware updates. For powering with an AC adapter use Part# PW-AC-USB.
Input / Output Ports:	

Size	3.5mm (1/8") mono miniphone
Port 1	Polarity sensitive (only connect properly wired cables!) MAX Input Voltage = 250 VDC MAX Input Current = 0.3 A
Port 2	Triggers in both polarities Normal Polarity Specs: MAX Input Voltage = 250 VDC MAX Input Current = 4.0 A for 20 microseconds, 0.25 A continuous Reverse Polarity Specs: MAX Input Voltage = 200 VDC MAX Input Current = 2.0 A for 20 microseconds (pulse only, no continuous contact)
Port 1 and Hot Shoe voltage present	Output Voltage = 3.1 VDC typical = safe for digital cameras
Port 1 and Hot Shoe triggering threshold	< 2.2 VDC
PORT 1 and Hot Shoe holding current:	0.0005 A

HOT SHOE NOTE: Some cameras may exhibit undesirable behavior if the RECEIVE unit is mounted in the camera hot shoe when that camera is being fired remotely. Some cameras' hot shoe and motor drive contacts may share some connections. This can cause the camera to lock up or stop operating normally. If your camera does not function properly in this mode then remove the unit from the camera's hot shoe.



Radio Information

- Transmit Output Power: 0.001 watt (1/1000 of a watt or 1 milliwatt)
- Typical Transmitter Output Duration: 0.0005 seconds (1/2000 second or 50 microseconds)
- Bandwidth: Narrowband, 70KHz TRANSMIT, 230KHz RECEIVE

PocketWizard Radio Frequencies:

Channel	Frequency	Unit	Digital Code
1 through 16	344.04 MHz	Classic, Plus, MAX, and MultiMAX	16 Bit
17	346.50 MHz	MultiMAX and MAX only	24 Bit (20 Bit in FAST MODE)
18	347.00 MHz		
19	347.50 MHz		
20	348.00 MHz		
21	348.50 MHz		
22	349.00 MHz		
23	349.50 MHz		
24	350.00 MHz		
25	350.50 MHz		
26	351.00 MHz		
27	351.50 MHz		
28	352.00 MHz		
29	352.50 MHz		
30	353.00 MHz		
31	353.50 MHz		
32	354.00 MHz		



Maximum and Minimum Settings

The following table details the maximum and minimum values allowed for each numeric entry setting available in the MultiMAX.

Setting	Maximum	Minimum
Contact Time	999.99 seconds or 16 minutes, 39.99 seconds	.01 seconds
Delay Time	9.9999 seconds	.0001 seconds (add 0.0005 to displayed value for RECEIVE units triggered via radio)
Interval (Intervalometer mode)	99:59:59 (1 second shy of 4 days, 4 hours or exactly 359,999 seconds)	1 second
Interval (Multipop mode)	999.99 seconds (16 minutes, 39.99 seconds)	.01 seconds
Count (for Load Count or Intervalometer / Multipop)	9999	0

Intervals are probably accurate to within +/- ~2.6 seconds per day based on the precision of the internal crystal operating at 30 parts per million.

The maximum run time for Multipop, with count set to 9999, is over 115 days.

The maximum run time for Intervalometer, with count set to 9999, is just over 114 years. You may need to use an AC adapter for this operation as batteries are unlikely to last 114 years.

Saved Settings

Settings are saved whenever the ***/MENU** key is pressed. The following settings are always RESET on normal power down:

- Counter (resets to saved load value if count is ↓, resets to 0 if count is ↑)
- Rear Curtain Sync (fraction display returns to 1/1)
- Any dynamic numeric entry screen displayed as unit is powered off will default to its previous saved setting. The screens affected are : Load counter, Delay time, and Interval (Multipop or Intervalometer)

The following settings are saved on power down:

Channel	Beep Mode	Delay Time	Zone	Contact Time	Counter Mode
Interval	Relay Mode	Load Count	Advanced Mode	Fast Mode	



TROUBLESHOOTING

When in doubt !

Many issues can be resolved by powering the unit off and then back on again or by resetting to factory default settings. Before proceeding to any other troubleshooting procedure follow these steps:

1. Set power to OFF
2. Wait 10 seconds or until display completely blanks
3. Set power to RECEIVE or TRANSMIT


Reset to Default Factory Settings


1. Set power switch to OFF
2. Press and hold **C** key
3. Continue to hold **C** and set the power switch to either RECEIVE or TRANSMIT
4. Release **C** key when CLEAR/RESET message appears

Default factory settings are as follows:

Channel	17
Transmitter Zones	A B C D L all enabled
Receiver Zone	A
Relay Mode	OFF
Operating mode	NORMAL
Contact Time	0.08 sec
Beep Mode	All
Fast Mode	OFF

Display Contrast	Medium
Delay Time	0.0100 sec
Equalize Calculated Time	0.1500 sec
Interval Time	00:00:01
Multipop Time	1.00 sec
Counter Mode	OFF
Counter Load	36

 The following indicators may operate erratically during reset, but will return to normal operation when reset completes: Battery Level, Frequency Lock, Beep Mode, and Channel.

 The CLEAR/RESET message also displays the software version installed in the unit. To view just the software version without losing settings refer to the **Software Version Display** section, Page 39, for more information.


SUSTAINING HIGH PERFORMANCE

Long distance performance from your **MultiMAX** depends on the orientation and position of the units.

Whenever possible, try to maintain a line of sight between the units and keep the antennas parallel. Make sure they are not near any large metal, concrete, or high water-content objects. People and trees are mostly water! Make sure they are not blocked by these objects or by hills.

Maintain at least 12" distance between antennas. Avoid direct antenna contact with anything metallic. "Dead spots" have a number of causes, but the solution is usually the same: move the unit a few inches or feet away from the problem area.

Positioning



Blocking Signal



Mounting suggestion.

Mount the remote **PocketWizard** so that the antenna is completely above the top edge of the flash pack and away from any metal (light modifiers, stands, etc.).

📌 Visit www.pocketwizard.com for more troubleshooting information. As more information becomes available it will be posted there. Be sure to check out the Frequently Asked Questions section on the website.

TIME CONVERSION CHARTS


Fractions to Decimal:

Here are some common photographic fractions in decimal values. All numbers are rounded to the nearest .0001 or 1/10,000th.

☞ These times are not Rear Curtain Sync times. These are precision numbers. Rear Curtain Sync numbers are always less than the exact conversions. Refer to the **Rear Curtain** section, Page 32, for more information.

Fraction	Decimal
1/2	0.5 seconds
1/4	0.25 seconds
1/8	0.125 seconds
1/15	0.0667 seconds
1/30	0.0333 seconds
1/60	0.0167 seconds
1/90	0.0111 seconds
1/125	0.008 seconds

Fraction	Decimal
1/180	0.0056 seconds
1/200	0.005 seconds
1/250	0.004 seconds
1/500	0.002 seconds
1/1000	0.001 seconds
1/2000	0.0005 seconds
1/4000	0.0003 seconds
1/8000	0.0001 seconds





For more information about using
your PocketWizard product visit:

www.PocketWizard.com